

Earth 50 Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Dimensional Category	Average Weight / Unit (kg)	Units per sqm	Pack Size	Durability Class	Slip Resistance	Liability To Effloresce	Lime Pitting Liability
Earth 50	Autumn Sunset			NSW	230	114	50	DPA1	2.72	37	480	Exposure Grade	P5	Slight	Slight
Earth 50	Gold n Copper			NSW	230	114	50	DPA1	2.72	37	480	General Purpose	P5	Slight	Slight
Earth 50	Sunburst Red			NSW	230	114	50	DPA1	2.72	37	480	Exposure Grade	P5	Slight	Slight
Earth 50	Slate			NSW	230	114	50	DPA1	2.72	37	480	General Purpose	P5	Slight	Slight
Earth 50	Firestone Red			NSW	230	114	50	DPA1	2.72	37	480	Exposure Grade	P5	Slight	Slight

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.



Please note: FRL applies up to 3m high - restrained on top and bottom.